

Performance Poly Rapid Dry Wood Floor Sealer

Dries Fast • Enhances Natural Wood Tones

Description

Rapid Dry Sealer seals wood and dries fast, allowing multiple coats in a day. An oil-modified formulation, the light amber color enhances the natural wood tones and is compatible with all Advantage Coatings' finishes.

Characteristics

- Penetrates and seals bare wood
- Rich oil color
- Highlights the grain of the wood
- High solid content = higher build
- Easy application and cleanup

Recommended Uses

Residential and commercial wood floors, especially as a base for Advantage Coatings' waterborne finishes

Technical Data

Sheen Level: N/A

Solid Content: 36%

VOC: does not exceed 550 grams per liter

Percent Cured: After 24 Hours: 70%

Fully Cured: 2 weeks

Shelf Life: 1 year

Storage and Working Temperature: 50° to 77°

Packaging: 5 gallon pail and 1 gallon jug

Clean Up: Mineral Spirits

Application Characteristics

Coverage rate: 700 - 800 square feet per gallon

Leveling: Excellent

Defoaming: Excellent

Dry Time: 2 - 4 hours

Application Tools: T-bar, cut-n-pad

Pot Life: N/A

Clarity: Light amber color



Advantage Coatings Technologies - Rapid Dry Sealer

DANGER! Contains Petroleum distillates. **DO NOT TAKE INTERNALLY!** Harmful if inhaled. Do not breathe vapors or mist. use with adequate ventilation. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved). May cause dizziness, headache, nausea. May cause eye, skin, nose or throat irritation. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. Keep away from heat, sparks and flames. Do not store above 120° F. Keep out of reach of children!

First aid: In case of eye contact, flush immediately with water for at least 15 minutes. Obtain medical attention. for skin, wash thoroughly with soap and water. If affected by inhalation, remove to fresh air. If continued difficulty is experienced, obtain medical attention immediately. If swallowed do not induce vomiting. Obtain medical attention immediately.

Storage and Disposal: Keep container closed when not in use. In case of spillage, absorb with inert material. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state or federal regulations.

DIRECTIONS FOR USE:

1. Sand and prepare floor using NOFMA-accepted methods.
2. Make a final cut with 80 grit paper and screen with 80-100 grit screen.
3. Vacuum and tack floor thoroughly.

STIR WELL BEFORE USING!

4. Apply RAPID DRY Sealer at a coverage rate of 600-700 sq. ft. per gallon with lambswool or synthetic floor coater. Allow to dry thoroughly with adequate ventilation (1.5-2 hours).
5. Abrade surface thoroughly with maroon abrasive pad (approx.: 200 grit) or a used 120-150 grit screen.
6. Vacuum and tack floor.
7. Apply Advantage Coatings Technologies finish at a coverage rate of 500 sq. ft. per gallon with a lambswool applicator or synthetic floor coater. Allow each coat to dry thoroughly.
8. For proper adhesion, abrade with maroon abrasive pad or used 120-150 grit screen between coats of finish. Allow final coat to dry a minimum 24 hours before use and avoid heavy traffic for 72 hours.

OSHA CLASS II (combustible liquid) flash point= 100 °F

DANGER: Rags, steel wool or waste soaked with Performance Poly Sealer or Finish may spontaneously catch fire if improperly discarded. immediately after use, place rags, steel wool or waste into sealed water filled metal container.

NOTE: There are no express or implied warranties, including warranties of merchantability or fitness for a particular purpose. Buyers remedies are limited to replacement or refund of purchase price. Manufacturer assumes no liability for injuries, incidental or consequential damages. User shall determine suitability or

Advantage Coatings Technologies
385 South Pierce Avenue, Suite E, Louisville, CO 80027-3054
(303) 499-1310
advantagecoatingstech.com
info@actfinish.com

